



ENERGREEN®

Professional Machines



POTENTE MOTORE DA
POWERFUL ENGINE WITH
50HP

RoboFIFTI 50HP



55

PENDENZA
SLOPE



* Super cingoli in gomma / Super rubber tracks
** Cingoli standard o con stiffe / Standard or studded tracks



**DESIGN A PROTEZIONE TOTALE
DESIGN FOR TOTAL PROTECTION**



**PROTEZIONI
LATERALI CONTRO
L'INTRUSIONE
DI VEGETAZIONE**
SIDE BODY PANELS
AGAINST INTRUSION
OF BUSHES
AND VEGETATION



**SOLLEVATORE
CON ATTACCO RAPIDO**
FRONT LIFTER WITH
QUICK ATTACHMENT
MOUNTING SYSTEM



**ROLL-BAR INTEGRATI
INTEGRATED ROLL BAR**



**CINGOLI IN GOMMA
RUBBER TRACKS**



**SUPER CINGOLI IN GOMMA
SUPER RUBBER TRACKS**



**CINGOLI CON STAFFE
STUDDED TRACKS**



**ATTACCHI RAPIDI CON PIASTRA
MULTICONNESSIONE (CEJN)**
HYDRAULIC COUPLINGS WITH
MULTI CONNECTION PLATE (CEJN)
OPTIONAL



**CHIODI
SPIKES
OPTIONAL**



**PENDENZA
SLOPE**

ROBOFIFTI

Pendenza massima / Maximum gradient	55°
Trasmissione / Transmission	Idrostatica / Hydrostatic
Velocità I° marcia / Low range speed	0 - 4 km/h / 0 - 2.50 mph
Velocità II° marcia / High range speed	0 - 7 km/h / 0 - 4.35 mph
Peso macchina / Machine Weight	1220 kg / 2645 lb

MOTORE / ENGINE

Marca / Brand	Perkins
Modello / Type	3 Cilindri Diesel / 3 Cylinders Diesel
Potenza / Power	50 hp (36 kW) Stage V - Tier5
Capacità carburante / Fuel tank	28,5 litri / 7,5 gal.
Giri al minuto al lavoro / Working RPM	2800 rpm

RADIOCOMANDO / REMOTE CONTROL

Marca / Brand	Autec
Frequenza radio / Radio frequency	870 Mhz (EU) - 915 Mhz (US)
Raggio d'azione / Working range	150 metri/meters / 492 ft
Joystick	Proporzionale / Proportional
Batteria / Battery	Ricaricabile / Rechargeable

TESTATA TRINCIANTE / MULCHER HEAD

Larghezza di taglio / Cutting width	1300 mm / 51.2 in
Tipo di pompa / Pump type	Pistoni / Pistons
Portata olio / Oil Flow	60 l/min / 15.8 gal/min
Pressione / Pressure	300 bar / 4351 psi
Peso / Weight	200 kg / 441 lb

TESTATA TRINCIANTE / MULCHER HEAD

Larghezza di taglio / Cutting width	1535 mm / 60.7 in
Tipo di pompa / Pump type	Pistoni / Pistons
Portata olio / Oil Flow	60 l/min / 15.8 gal/min
Pressione / Pressure	300 bar / 4351 psi
Peso / Weight	310 kg / 683 lb

HEAD 130



HEAD 155



ENERGREEN®
Professional Machines

ENERGREEN S.P.A. · Via Sabbioni, 16
36026 Poiana Maggiore (Vicenza) · Italy
Tel. +39 0444 1511200 · Fax +39 0444 1511252
commerciale@energreen.it · www.energreen.it

WWW.ENERGREEN.IT

